

# fade Acoustic

## ALBUS

Item no. 14711



### Product description and areas of application

The fade® Acoustic Plaster – ALBUS comes ready mixed in 10 kg bags. The high quality and microporous acoustical plaster is manufactured in Denmark using only high quality materials. The acoustic plaster is produced from vulcanized perlite to ensure the best acoustical performance when installed onto ceilings or walls.

#### Product data

<b>Fade Acoustic - ALBUS</b>	Acoustic plaster containing vulcanized perlite, water based cellulose.
<b>Item no.</b>	14711
<b>Unit description</b>	Bag containing 10 kg
<b>Usage per m<sup>2</sup></b>	Approx. 4 kg
<b>Effect per unit (13,3 litre)</b>	Approx. 2,5 - 3 m <sup>2</sup>
<b>Grain size</b>	2 mm
<b>Standard colour</b>	NCS S 0500-N / RAL 9016
<b>Other colours</b>	Any colour
<b>Mixing instructions</b>	The product comes ready-mixed
<b>Technical data</b>	Anti-static & mold-, UV- and humidity resistant. Class A Fire Testing. VOC: 0,014 mg/m <sup>2</sup> h
<b>Storage</b>	Always store in containers of the same material as the original container. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.  Storage temperature: Frost free  Shelf life: 12 months