

DECLARATION OF PERFORMANCE

Construction Products Regulation (EU) No. 305/2011

No. DOP001-F-211201**1. Unique identification of the product-type****fade® Acoustic Plaster****2. Element allowing identification of the construction product**

fade® Acoustic Plaster ALBUS

fade® Acoustic Plaster PLUS+

3. Intended use of the construction product, in accordance with the applicable harmonized specification

Suspended ceiling membrane components for use internally in buildings to produce an installed suspended ceiling

4. Name, registered trade name and contact address of the manufacturer

fade® Acoustic Ceilings ApS

Stamholmen 157, DK-2650, Hvidovre, Denmark

www.fadeceilings.com

5. Name and contact address of the authorized representative

Not applicable

6. System(s) of Assessment and Verification of Constancy of Performance of the construction product

System 1 (Reaction to fire), System 4 (Release of formaldehyde, Sound absorption)

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard

RISE Research Institutes of Sweden (notified body 0402) performed a determination of the product type on the basis of type testing, type calculation, tabulated values or descriptive documentation of the product; an initial inspection of the manufacturing plan and of factory production control; a continuous surveillance, assessment and evaluation of factory production control under for properties under System 1 and issued a Certificate of Performance.

A determination of the product-type on the basis of type testing, type calculation, tabulated values or descriptive documentation of the product properties under System 4 was performed. No tasks for the notified body.

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued

Not applicable

9. Declared performance

Essential characteristics	Performance	Harmonized Technical Specification
Reaction to fire	A2-s1,d0	EN13964:2014
Release of formaldehyde	E1	
All other characteristics	NPD	

Sound absorption (Harmonized Technical Specification: EN13964:2014)

Product	a_w	Product	a_w
PLUS+ (15 mm)	0,65 (ODS 15 mm)	ALBUS (20 mm)	0,7 (ODS 20 mm) 0,9 (ODS 50 mm) 0,85 (ODS 200 mm)
PLUS+ (20 mm)	0,7 (ODS 20 mm)	ALBUS (25 mm)	0,8 (ODS 25 mm)
PLUS+ (25 mm)	0,8 (ODS 25 mm) 0,85 (ODS 200 mm)	ALBUS (40 mm)	1,0 (ODS 40 mm) 1,0 (ODS 200 mm)
PLUS+ (40 mm)	0,9 (ODS 40 mm) 0,9 (ODS 200 mm)		

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4. Signed for and on behalf of the manufacturer:

Mikael Olsson

Mikael Olsson
 Innovation Manager
 Eslöv, 2021-12-01