


fade acoustic plaster

ALBUS

Item no. 14717



Product description and areas of application

The fade® acoustic plaster – ALBUS comes ready mixed in 10kg (22.05lb) buckets. The high quality and microporous acoustical plaster is manufactured in Denmark using only high quality materials. The acoustic plaster is produced from vulcanized perlite to ensure the best acoustical performance when installed onto ceilings or walls.

Product data

| | |
|---|--|
| fade® Acoustic - ALBUS | Acoustic plaster containing vulcanized perlite, water based cellulose. |
| Item no. | 14717 |
| Unit description | Bucket containing 10kg (22.05lb) |
| Usage per m ² (sq') | Approx. 4kg (8.82lb) |
| Effect per unit (13.3L (3.32U.S. gallons)) | Approx. 2.5 - 3m ² (26.90-32.28sq') |
| Grain size | 2mm (.08") |
| Standard color | NCS S 0500-N / RAL 9010 |
| Other colors | Any color |
| Mixing instructions | The product comes ready-mixed |
| Technical data | Anti-static & mold-, UV- and humidity resistant. Class A Fire Testing. VOC: 0,02g/L |
| Storage | Always store in containers of the same material as the original container. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Storage temperature: Frost free Shelf life: 12 months |