

fade acoustic plaster

PLUS+

Item no. 14719



Product description and areas of application

The fade® acoustic plaster – PLUS+ comes pre-mixed in 7.5kg (16.53lb) buckets. The high quality and microporous acoustical plaster is manufactured in Denmark using only high quality materials. The acoustic plaster is produced from vulcanized perlite to ensure the best acoustical performance when installed onto ceilings or walls.

Product data

fade® Acoustic - PLUS+	Acoustic plaster containing vulcanized perlite, water based cellulose.
Item no.	14719
Unit description	Bucket containing 7.5kg (16.53lb)
Usage per m² (sq')	Approx. 2.5kg (5.5lb)
Effect per unit (7.5kg (16.53lb))	Approx. 2.5 - 3m ² (26.90-32.28sq')
Grain size	0,7mm (7/254")
Standard color	NCS S 0300-N / RAL 9016
Other colors	Any color
Mixing instructions	Add approximately 900-1200ml (30.43-40.58fl oz) of water to every 7.5kg (16,53lb) bucket and mix well
Technical data	Anti-static & mold-, UV- and humidity resistant. Class A Fire Testing. VOC: 0,02g/L
Storage	Always store in containers of the same material as the original container. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Storage temperature: Frost free Shelf life: 12 months